



# Vision

## EasyPlus

Special products  
vending solutions

The Vision EasyPlus range features a backlit front cover that allows offering special products that need higher insulation or that cannot be exposed to direct sunlight. Its flexible channel adjustment system allows incorporating new products at any time without using tools.

**FEATURES**

- Temperature: Under 5°C.
- 6 trays of up to 10 channels and 2 trays of up to 7 channels.
- FIFO (First In First Out) System. Product dispensing according to loading order.
- Correct sale detection with photocells.
- LED lighting system with on/off programming.
- Continuous performance self-testing.
- Health timer to prevent selling out-of-date products. Programmable expiration date by selection or channel.
- Flexible setup and programming. Its channel adjustment system allows incorporating new products at any time without using tools.
- Adjustable motor torque for each selection.
- Power mains: 230V, 50 Hz.
- Estimated energy consumption: 650 watts.

**STRUCTURE**

- Modular cabinet structure treated against rust and corrosion.
- Vandal-proof security lock with three anchor points.
- High-capacity cash box with lock and optional auto-locking during extraction.
- Injected foam insulation system to guarantee efficient cooling and lower energy consumption.

**CREDIT MANAGEMENT**

- MDB or Executive protocol.
- Innovative Jofemar coin mechanism with five return tubes for up to five different coin values and the most reliable fraud-prevention systems.
- Allows installation of card and banknote readers.

**PROGRAMMING**

- General on site programming and display system for the accounting data, accessible from inside the machine.
- Compatible with the Jofemar EasyFlash tooling for stock control and accounting.
- Compatible with the latest telemetry systems for the end-to-end remote machine management.
- RS232 port with accounting data output.

**OPTIONS**

- Jofemar banknote reader.
- Jofemar J130 card/key reader or any card reader that uses the MDB protocol.
- Vandal-proof coin entry.
- Modem installation and Vending Track communication interface.
- Online operation with real-time control of users and sales.

	EASYPLUS
Temperature	Under 5°C
Maximum capacity	6 trays of up to 10 channels and 2 trays of up to 7 channels
Size (mm)	1,830 x 803 x 970
Weight	297
Energy supply	230 V, 50 Hz*
Cooling unit	CFC-free R-134a

\*Check for other voltages.



VANDAL-PROOF LOCK



OPTIMISED CAPACITY AND VOLUME



ENERGY-SAVING LED LIGHTING



BANKNOTE AND COIN MECHANISM PAYMENT SYSTEMS



EASYFLEX DELIVERY SYSTEM



HEALTH TIMER: EXPIRATION PROGRAMMING BY TEMPERATURE



PRODUCT DELIVERY DETECTION PHOTOCELLS



Ctra. Marcilla km 2  
31350 PERALTA. Navarra SPAIN  
Tel. +34 948 75 12 12  
Fax +34 948 75 04 20

[www.jofemarm vending.com](http://www.jofemarm vending.com)

