



Vision

Multiseller

Sensitive
products sale

Vision Multiseller is the most appropriate solution to vend high ticket items and/or sensitive products and packages, as it features a soft delivery elevator that delivers at a waist-height point, with soft precise movements. Keeps snacks and drinks at room temperature

FEATURES

- Capacity for up to 8 height-adjustable trays with up to 7 channels each.
- Room temperature.
- FIFO (First In First Out) System. Continues renewal with the freshest product. Product dispensing according to loading order.
- Correct sale detection with photocells.
- LED lighting system with on/off programming.
- 1462 x 473.5 mm glass front door.
- Continuous performance self-testing.
- Adjustable motor torque for each selection.
- Flexible setup and programming. Its channel adjustment system allows incorporating new products at any time without using tools.
- Programmable motor torque for each selection.
- Power mains: 230 V, 50 Hz.
- Estimated energy consumption: 25 watts.

STRUCTURE

- Modular cabinet structure treated against rust and corrosion.
- Vandal-proof security lock with three anchor points.
- High-capacity cash box with lock and optional auto-locking during extraction.
- Injected foam insulation system that guarantees efficient cooling and lower energy consumption.

CREDIT MANAGEMENT

- MDB or Executive protocol.
- Innovative Jofemar coin mechanism with five return tubes for up to five different coin values and the most reliable fraud-prevention systems.
- Card and banknote readers fitted.

PROGRAMMING

- General on site programming and display system for the data accounting, accessible from inside the machine.
- Compatible with the Jofemar EasyFlash handheld terminal for stock control and accounting.
- Compatible with the latest telemetry systems for the end-to-end remote machine management.
- RS232 port with accounting data output.

OPTIONS

- Jofemar banknote reader.
- Jofemar J130 card/key reader or any card reader that uses the MDB protocol.
- Vandal-proof coin entry.
- Modem installation and Vending Track communication interface.
- Online operation with real-time control of users and sales.
- Fitted to manage up to two slave vending machines for higher capacity and number of selections.
- External microwave ovens detached column controlled by the master machine. Its availability and heating times depend on the selections.

	MULTISELLER
Temperature	Room temperature
Maximum capacity	8 trays of up to 7 channels
Elevator	Yes
Size (mm)	1,830 x 803 x 935
Weigh	296 kg
Energy supply	230 V, 50 Hz*
Cooling unit	No

*Check for other voltages.



VANDAL-PROOF LOCK



OPTIMISED CAPACITY AND VOLUME



ENERGY-SAVING LED LIGHTING



BANKNOTE AND COIN MECHANISM PAYMENT SYSTEMS



EASYFLEX DELIVERY SYSTEM



EXPIRATION PROGRAMMING



PRODUCT DELIVERY DETECTION PHOTOCELLS



ELEVATOR



Ctra. Marcilla km 2
31350 PERALTA. Navarra SPAIN
Tel. +34 948 75 12 12
Fax +34 948 75 04 20

www.jofemarm vending.com

