

Vision

E-S
BLUETEC

Multiproduct
dispensing
solutions



Suitable for almost any kind of product the Vision E-S range significantly increases the number of channels and storage capacity as it can be connected to a master machine or to a master payment module. Optionally, it can feature a cooling unit.



ENERGY CLASS
REGULATION (EU)
2019/2018

FEATURES

- Temperature: with or without cooling unit.
- Capacity for 6 and 2 height-adjustable trays with up to 10 channels each.
- FIFO (First In First Out) System. Product dispensing according to loading order.
- Correct sale detection with photocells.
- LED lighting system with on/off programming.
- 1169 x 714 mm glass front door.
- Continuous performance self-testing.
- Health timer to prevent selling out-of-date products. Programmable expiration date by selection or channel.
- Flexible setup and programming. Its channel adjustment system allows incorporating new products at any time without using tools.
- Adjustable motor torque for each selection.
- Power mains: 230 V, 50 Hz.
- Estimated energy consumption: 650 watts.

STRUCTURE

- Modular cabinet structure treated against rust and corrosion.
- Vandal-proof security lock with three anchor points.
- Injected foam insulation system to guarantee efficient cooling and lower energy consumption.

CREDIT MANAGEMENT

- Through the master machine, Vision or Coffeemar machines.
- Through the payment pod.

PROGRAMMING

- Through the Main, Vision or Coffeemar machines.
- Through the payment module.

OPTIONS

- It can include cooling module.
- Side payment module for an independent operation.
- Spiral channels in the upper trays.

	SATELLITE REFRIGER V7
Temperature	With/Without cooling unit
Maximum capacity	6 trays of up to 10 channels and 2 trays of up to 7 channels
Elevator	No
Size (mm)	1,830 x 803 x 935
Weight	297 kg
Energy supply	230 V, 50 Hz*
Cooling unit	Optional

*Check for other voltages.



VANDAL-PROOF
LOCK



OPTIMISED
CAPACITY AND
VOLUME



ENERGY-SAVING
LED LIGHTING



EASYFLEX
DELIVERY SYSTEM



PRODUCT DELIVERY
DETECTION
PHOTOCELLS



IMPROVED
DESIGN



Ctra. Marcilla km 2
31350 PERALTA. Navarra SPAIN
Tel. +34 948 75 12 12
Fax +34 948 75 04 20
www.jofemar.com

